

Slash® Brushless (Model 58134-4) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

	Bearings & Bushings	6844-	Body, Slash® 4X4 (also fits Slash® VXL & Slash® 2WD), orange
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)	ORNG	and blue (painted, decals applied) (assembled with front & rear latches for clipless mounting)
5114	Ball bearings, blue rubber shield (5x8x2.5mm) (2)	6928R	Body, Slash® 4X4 (also fits Slash® VXL & Slash® 2WD), red &
2545	Bushings (plastic) (5x8x2.5mm) (4)		blue (painted, decals applied)
1985	PTFE-coated Washers, 5x8x0.5mm (20) (use with ball bearings)	6928-RED	Body, Slash® 4X4 (also fits Slash® VXL & Slash® 2WD), red & blue (painted, decals applied) (assembled with front & rear
	Body & Accessories		latches for clipless mounting)
1926	Antenna caps, vinyl (2)/ antenna spool	5824-RED	Body, Slash® 4X4 (also fits Slash® VXL & Slash® 2WD), red
1726 5851X	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) Body, Slash® 2WD (also fits Slash® VXL & Slash® 4X4), blue		(painted, decals applied) (assembled with front & rear latches for
000170	(painted, decals applied)	5848-RNR	clipless mounting) Body, Slash® 4X4 (also fits Slash® VXL & Slash® 2WD), Rock n'
5851-BLUE	Body, Slash® 2WD (also fits Slash® VXL & Slash® 4X4), blue	00-10 111111	Roll (painted, decals applied) (assembled with front & rear
	(painted, decals applied) (assembled with front & rear latches for clipless mounting)		latches for clipless mounting)
5851G	Body, Slash® 2WD (also fits Slash® VXL & Slash® 4X4), green &	6811	Body, Slash® 4X4 (clear, requires painting)/ window masks/ decal sheet
	blue (painted, decals applied)	6932-GRN	
5851-GRN	• • • • • • • • • • • • • • • • • • • •		with front & rear body mount latches for clipless mounting)
	blue (painted, decals applied) (assembled with front & rear latches for clipless mounting)	5849	Body, Slash® 4X4, Hawaiian graphics (painted, decals applied)
5924-GRN		6965R	Body, Slash® 4X4, heavy duty (also fits Slash® VXL & Slash® 2WD) (clear, requires painting)/ window masks/ decal sheet
	(painted, decals applied) (assembled with front & rear latches for		(requires #6967 latches and #6966 latch mounts for clipless
E0E4T	clipless mounting)		mounting)
5851T	Body, Slash® 2WD (also fits Slash® VXL & Slash® 4X4), orange & blue (painted, decals applied)	6811R	Body, Slash® 4X4, heavy duty (clear, requires painting)/ window
5851-	Body, Slash® 2WD (also fits Slash® VXL & Slash® 4X4), orange	5824	masks/ decal sheet Body, Slash® 4X4, Keegan Kincaid (painted, decals applied)
ORNG	& blue (painted, decals applied) (assembled with front & rear	5850	Body, Slash® 4X4, orange (painted, decals applied)
5851P	latches for clipless mounting) Body, Slash® 2WD (also fits Slash® VXL & Slash® 4X4), pink &	5850X	Body, Slash® 4X4, orange (painted, decals applied)
00011	purple (painted, decals applied)	6932L	Body, Slash® 4X4, ProGraphix® (graphics are printed, requires
5851-PINK	Body, Slash® 2WD (also fits Slash® VXL & Slash® 4X4), pink &		paint & final color application)/ body mount latch (front & rear)/ latch mounts/ decal sheet
	purple (painted, decals applied) (assembled with front & rear latches for clipless mounting)	5812	Body, Slash® 4X4, ProGraphix® (Graphics are printed, requires
5851R	Body, Slash® 2WD (also fits Slash® VXL & Slash® 4X4), red &	00001	paint & final color application)/ decal sheet
	blue (painted, decals applied)	6928L	Body, Slash® 4X4, ProGraphix® (graphics are printed, requires paint & final color application)/ decal sheet
5851-RBLU	Body, Slash® 2WD (also fits Slash® VXL & Slash® 4X4), red &	6811X	Body, Slash® 4X4, ProGraphix® (Graphics are printed, requires
	blue (painted, decals applied) (assembled with front & rear latches for clipless mounting)		paint & final color application)/ decal sheet
5851	Body, Slash® 2WD (also fits Slash® VXL & Slash® 4X4), red	5824R	Body, Slash® 4X4, red (painted, decals applied)
	(painted, decals applied)	6932-RED	Body, Slash® 4X4, red (painted, decals applied) (assembled with front & rear body mount latches for clipless mounting)
5851-RED	Body, Slash® 2WD (also fits Slash® VXL & Slash® 4X4), red	5848	Body, Slash® 4x4, Rock n' Roll (painted, decals applied)
	(painted, decals applied) (assembled with front & rear latches for clipless mounting)	6849	Body, Slash® 4X4/Slash®, Fox Edition (painted, decals applied)
5924-RED	Body, Slash® 2WD (also fits Slash® VXL & Slash® 4X4), red	6849R	Body, Slash® VXL 2WD (also fits Slash® 4X4), Fox® (painted,
	(painted, decals applied) (assembled with front & rear latches for	6849-FOX	decals applied) Body, Slash® VXL 2WD (also fits Slash® 4X4), Fox® Edition
5855	clipless mounting) Body, Slash® 2WD, ProGraphix® (also fits Slash® VXL & Slash®	00-10 1 070	(painted, decals applied) (assembled with front & rear latches for
	4X4) (graphics are printed, requires paint & final color		clipless mounting)
	application)/ decal sheet	6812G	Body, Slash® VXL 2WD (also fits Slash® 4X4), green & blue (painted, decals applied)
5851L	Body, Slash® 2WD, ProGraphix® (graphics are printed, requires paint & final color application)/ decal sheet	6812-GRN	
6965	Body, Slash® 4X4 (also fits Slash® VXL & Slash® 2WD) (clear,		(painted, decals applied) (assembled with front & rear latches for
	requires painting)/ window masks/ decal sheet (requires #6967	COAST	clipless mounting)
60206	latches and #6966 latch mounts for clipless mounting)	6812T	Body, Slash® VXL 2WD (also fits Slash® 4X4), orange & blue (painted, decals applied)
6928G	Body, Slash® 4X4 (also fits Slash® VXL & Slash® 2WD), green & blue (painted, decals applied)	6812-	Body, Slash® VXL 2WD (also fits Slash® 4X4), orange & blue
6928-GRN	Body, Slash® 4X4 (also fits Slash® VXL & Slash® 2WD), green &	ORNG	(painted, decals applied) (assembled with front & rear latches for
	blue (painted, decals applied) (assembled with front & rear	6812R	clipless mounting) Body, Slash® VXL 2WD (also fits Slash® 4X4), red (painted,
6844-GPN	latches for clipless mounting) Body, Slash® 4X4 (also fits Slash® VXL & Slash® 2WD), green	001210	decals applied)
0044-GKN	and blue (painted, decals applied) (assembled with front & rear	6812-RED	Body, Slash® VXL 2WD (also fits Slash® 4X4), red (painted,
	latches for clipless mounting)		decals applied) (assembled with front & rear latches for clipless
5849-HWN	Body, Slash® 4X4 (also fits Slash® VXL & Slash® 2WD),	5915	mounting) Body, Slash® VXL 2WD, ProGraphix® (also fits Slash® 4X4)
	Hawaiian graphics (painted, decals applied) (assembled with front & rear latches for clipless mounting)		(graphics are printed, requires paint & final color application)/
5824-BLUE	Body, Slash® 4X4 (also fits Slash® VXL & Slash® 2WD), Keegan	00401	decal sheet
	Kincaid (painted, decals applied) (assembled with front & rear	6812L	Body, Slash® VXL, ProGraphix® (graphics are printed, requires paint & final color application)/ decal sheet
6928T	latches for clipless mounting) Body, Slash® 4X4 (also fits Slash® VXL & Slash® 2WD), orange	2514	Decal sheet, racing sponsors
JJ201	& blue (painted, decals applied)	5813	Decal Sheet, Slash
6928-	Body, Slash® 4X4 (also fits Slash® VXL & Slash® 2WD), orange	6966	Latch mounts/ retainers (front & rear, left & right)
ORNG	& blue (painted, decals applied) (assembled with front & rear	6967	Latch, body mounts (front & rear)
5850-	latches for clipless mounting) Body, Slash® 4X4 (also fits Slash® VXL & Slash® 2WD), orange	9950 5846	Official Team Traxxas® racing decal set(flag logo/ 6-color) Paint masks, body
ORNG	(painted, decals applied) (assembled with front & rear latches for	30-10	· ····································
	clipless mounting)		

Page 2 Slash® Brushless: TQ™ 2.4GHz Radio (Model 58134-4) Parts List

	Chassis & Attachments	9461T	Wheels, wheelie bar, 6061-T6 aluminum (gray-anodized) (2)/ 5x8x2.5mm ball bearings (4)/ o-rings (2)/ 5x8x0.3mm TW (2)
5526	Antenna crimp nut, aluminum (blue-anodized)/ antenna nut tool	9461G	Wheels, wheelie bar, 6061-T6 aluminum (green-anodized) (2)/
5526R 9463X	Antenna crimp nut, aluminum (red-anodized)/ antenna nut tool Axle, wheelie bar, 6061-T6 aluminum (blue-anodized) (1)/ 3x12	9461A	5x8x2.5mm ball bearings (4)/ o-rings (2)/ 5x8x0.3mm TW (2) Wheels, wheelie bar, 6061-T6 aluminum (orange-anodized) (2)/
9463	BCS (with threadlock) (2) Axle, wheelie bar, 6061-T6 aluminum (gray-anodized) (1)/ 3x12	9461P	5x8x2.5mm ball bearings (4)/ o-rings (2)/ 5x8x0.3mm TW (2) Wheels, wheelie bar, 6061-T6 aluminum (pink-anodized) (2)/
9463G	BCS (with threadlock) (2) Axle, wheelie bar, 6061-T6 aluminum (green-anodized) (1)/ 3x12	9461R	5x8x2.5mm ball bearings (4)/ o-rings (2) 5x8x0.3mm TW (2) Wheels, wheelie bar, 6061-T6 aluminum (red-anodized) (2)/
9463A	BCS (with threadlock) (2) Axle, wheelie bar, 6061-T6 aluminum (orange-anodized) (1)/ 3x12		5x8x2.5mm ball bearings (4)/ o-rings (2)/ 5x8x0.3mm TW (2)
403A	BCS (with threadlock) (2)	9461	Wheels, wheelie bar, black (26mm (2), 18mm (2))
9463P	Axle, wheelie bar, 6061-T6 aluminum (pink-anodized) (1)/ 3x12	2200	Differential Components
9463R	BCS (with threadlock) (2) Axle, wheelie bar, 6061-T6 aluminum (red-anodized) (1)/ 3x12 BCS (with threadlock) (2)	2380 2381X	Differential, complete (fits 1/10-scale 2WD Rustler®, Bandit, Stampede®, Slash®) Main diff with steel ring gear/ side cover plate/ screws (Bandit,
940	Body mounts, front & rear	23017	Stampede®, Rustler®)
624	Box, receiver (sealed)/ foam pad/ silicone grease/ 3x8mm BCS (2)/ 2.5x8mm CS (2)/ 3x6mm BCS (2)	2382	Planet gears (4)/ planet shafts (4)/ sun gears (2)/sun gear alignment shaft (1) all hardened steel
5835X	Bumper, front/ bumper mount (fits 2WD Slash®) (for LED light kit installation)	2388X	Planetary gear differential with steel ring gear (complete) (fits Bandit, Stampede®, Rustler®)
5835	Bumper, front/ bumper mount, front (black)	5169	Screws, 2.6x8mm countersunk machine (6) (EZ Start 2 motor)
5835P 5838	Bumper, front/ bumper mount, front (pink)	1647	Silicone Grease
1030	Bumper, rear/ bumper mount (fits 2WD Slash®) (for LED light kit installation)		Driveline Components
5836	Bumper, rear/ bumper mount, rear (black)	5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)
5836P	Bumper, rear/ bumper mount, rear (pink)	9059X 9057X	Cross pin (2)/ drive pin (2) (repairs 1 axle shaft) Differential output shafts, steel-splined constant-velocity (2)
5830 5832	Chassis conversion kit, low CG (Slash®)	4628R	Differential output sharts, steer-splined constant-velocity (2) Differential output yokes, black (2)/ 3x5mm countersunk screws (2)/
5832 5832A	Chassis, low CG (black) Chassis, low CG (blue)		screw pin (2)
5832G	Chassis, low CG (grey)	4628X	Differential output yokes, hardened steel (w/ U-joints) (2)
5822	Chassis, Slash	6828X 6852A	Differential output yokes, heavy duty (2)/ screw pin (2) Driveshaft assembly, rear, extreme heavy duty (1) (left or right)
822A	Chassis, Slash (black)	0002A	(fully assembled, ready to install)/ screw pin (1)
827	Hold down, battery/ hold down retainer/ battery post/ foam spacer/ angled body clip	6852X	Driveshaft assembly, rear, heavy duty (1) (left or right) (fully
827X	Hold down, battery/ hold down retainer/ battery post/ foam	COFOR	assembled, ready to install)/ screw pin (1)
	spacer/ angled body clip (allows for installation of taller, multi-	6852R	Driveshafts, rear, steel-spline constant-velocity (complete assembly) (2)
004	cell batteries)	9052X	Driveshafts, rear, steel-spline constant-velocity (complete
831 831A	Lower chassis, low CG (black) Lower chassis, low CG (blue)		assembly) (2)
831G	Lower chassis, low CG (grey)	1953	Half shaft pro-pack (internal-splined (6)/ external-splined (6)
823	Nerf bars, chassis (black)	6750	(plastic shafts only) Half shaft, external splined (steel-spline constant velocity) (1)
833	Nerf bars, low CG (black)	9055X	Half shaft, external splined (steel-spline constant velocity) (1)
833A	Nerf bars, low CG (blue)	6751	Half shaft, internal splined (steel-spline constant velocity) (1)
5 833G 5625	Nerf bars, low CG (grey) Seal kit, receiver box (includes o-ring, seals, and silicone grease)	9056X	Half shaft, internal splined (steel-spline constant velocity) (1)
9462X	Side plates, wheelie bar, blue (aluminum) (2)	6850X	Half shafts, heavy duty (external splined (2)/ internal splined (2)) metal u-joints (4)
9462	Side plates, wheelie bar, charcoal gray (aluminum) (2)	1951	Half shafts, long truck (external-splined (2) & internal-splined (2)/
9462G	Side plates, wheelie bar, green (aluminum) (2)		metal U-joints (4)
9462A 9462P	Side plates, wheelie bar, orange (aluminum) (2) Side plates, wheelie bar, pink (aluminum) (2)	9058X	Rebuild kit, steel-splined constant-velocity driveshafts (includes
9462R	Side plates, wheelie bar, red (aluminum) (2)	6757	pins and hardware for one axle shaft) Rebuild kit, steel-splined constant-velocity driveshafts (includes
5837	Skidplates, front & rear (black)	0.0.	pins, dustboots, lube, and hardware)
5185	Tires, rubber (2) (fits Traxxas® wheelie bar wheels)	3752	Stub axle carriers (2) (requires 5x11x4mm bearings)
1974	Wheelie Bar arm (1)/ connector (1)/ 3x12 SS (hex drive) (4)	3652A	Stub axle carriers, Rustler®/Stampede®/Bandit (2), 6061-T6
3677X 3677A	Wheelie bar mount (1) / hardware (blue) Wheelie bar mount (1) / hardware (green)	3652G	aluminum (blue-anodized)/ 5x11mm ball bearings (4) Stub axle carriers, Rustler®/Stampede®/Bandit (2), 6061-T6
3677P	Wheelie bar mount (1) / hardware (gireen) Wheelie bar mount (1) / hardware (pink)	30320	aluminum (green-anodized)/ 5x11mm ball bearings (4)
3677	Wheelie bar mount (1)/ hardware (Stampede®, Rustler®, Bandit	3652T	Stub axle carriers, Rustler®/Stampede®/Bandit (2), 6061-T6
1464	series)	3652D	aluminum (orange-anodized)/ 5x11mm ball bearings (4) Stub axle carriers, Rustler®/Stampede®/Bandit (2), 6061-T6
9464 8678	Wheelie bar mount (heavy duty) Wheelie bar, assembled (black) (fits Slash®, Stampede®,	3652P	aluminum (pink-anodized)/ 5x11mm ball bearings (4)
8678X	Rustler®, Bandit® series) Wheelie bar, assembled (blue) (fits Stampede®, Rustler®, Bandit	3652X	Stub axle carriers, Rustler®/Stampede®/Bandit (2), 6061-T6 aluminum (red-anodized)/ 5x11mm ball bearings (4)
	series)	2754	Stub axle pins (4)
8678A	Wheelie bar, assembled (green) (fits Slash®, Stampede®,	9053X	Stub axle, rear, steel-splined constant velocity (1)
1679T	Rustler®, Bandit® series) Wheelig har assembled (orange) (fits Slash®, Stampede®	6753 2753X	Stub axle, rear, steel-splined constant velocity (1) Stub axles, rear (2)
678T 678P	Wheelie bar, assembled (orange) (fits Slash®, Stampede®, Rustler®, Bandit® series) Wheelie bar, assembled (pink) (fits Slash, Stampede®, Rustler®,	6853X	Stub axles, rear, heavy duty (2)/pins (2)
0101	Bandit series)		Front Suspension & Steering
678R	Wheelie bar, assembled (red) (fits Slash®, Stampede®, Rustler®, Bandit® series)	3637 5116	Axles (front) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2)
460	Wheelie bar, black (assembled)/ wheelie bar mount	2530	Bulkhead (front) (black)
460X	Wheelie bar, black chrome (assembled)/ wheelie bar mount	2530A	Bulkhead (front) (grey)
976	Wheels (4)/ Axles (2), for Maxx® Wheelie Bar	2545	Bushings (plastic) (5x8x2.5mm) (4)
	Wheels, aluminum (blue-anodized) (2)/ 5x8mm ball bearings (4)/ axles (2)/ rubber tires (2)	3632 3632A	Caster blocks (l&r) (30-degree) Caster blocks, 30-degree, blue-anodized 6061-T6 aluminum (left
5186A		JJU27	Sicono, co acgree, Side-dilodized ovoi-10 didilililidili (lett
	Wheels, aluminum (red-anodized) (2)/ 5x8mm ball bearings (4)/	3632G	& right)/ suspension screw pin (2) Caster blocks, 30-degree, green-anodized 6061-T6 aluminum (le
5186A 5186 9461X	* *	3632G	& right)/ suspension screw pin (2) Caster blocks, 30-degree, green-anodized 6061-T6 aluminum (le & right)/ suspension screw pin (2)

Page 3 Slash® Brushless: TQ™ 2.4GHz Radio (Model 58134-4) Parts List

Page 3	Siash® Brushiess: I Q''" 2.46mz Radio (Model 5613		
3632P	Caster blocks, 30-degree, pink-anodized 6061-T6 aluminum (left	5347	Rod ends, Revo® (large) with hollow balls (12)
	& right)/ suspension screw pin (2)	2742X	Rod ends, short (6)/ hollow balls (6)
3632X	Caster blocks, 30-degree, red-anodized 6061-T6 aluminum (left &	3215	Screws, 2.5x6mm cap-head machine (hex drive) (6)
50.47	right)/ suspension screw pin (2)	3965	Screws, 2.5x8mm cap-head machine (6)
5347	Rod ends, Revo® (large) with hollow balls (12)	2577	Screws, 3x10mm button-head machine (hex drive) (6)
3646	Screws, 3x15mm flat-head machine (hex drive) (6)	2578	Screws, 3x12mm button-head machine (hex drive) (6)
3744 3639	Servo saver w/ adapters Shock tower (front)	2552	Screws, 3x12mm countersunk machine (6) (hex drive)
3743	Steering bellcranks (l&r)/ draglink	2579	Screws, 3x15mm button-head machine (hex drive) (6)
3743A	Steering belicranks, drag link (blue-anodized 6061-T6 aluminum)/	2586	Screws, 3x15mm cap-head machine (hex drive) (6)
37434	5x8mm ball bearings (4)/ hardware (assembled)	3646	Screws, 3x15mm flat-head machine (hex drive) (6)
3743G	Steering bellcranks, drag link (green-anodized 6061-T6	2583 2580	Screws, 3x18 button-head machine (hex drive) (6) Screws, 3x20mm button-head machine (hex drive) (6)
	aluminum)/ 5x8mm ball bearings (4)/ hardware (assembled)	2591	Screws, 3x23mm button-head machine (hex drive) (6)
3743T	Steering bellcranks, drag link (orange-anodized 6061-T6	2582	Screws, 3x30mm button-head machine (hex drive) (6)
	aluminum)/ 5x8mm ball bearings (4)/ hardware (assembled)	2592	Screws, 3x40mm button-head machine (hex drive) (6)
3743P	Steering bellcranks, drag link (pink-anodized 6061-T6 aluminum)/	2575	Screws, 3x6mm button-head machine (hex drive) (6)
	5x8mm ball bearings (4)/ hardware (assembled)	3932	Screws, 3x6mm flat-head machine (hex drive) (6)
3743X	Steering bellcranks, drag link (red-anodized 6061-T6 aluminum)/ 5x8mm ball bearings (4)/ hardware (assembled)	2576	Screws, 3x8mm button-head machine (hex drive) (6)
6845X	Steering bellcranks/ servo saver/ servo saver spring/ servo	3931	Screws, 3x8mm flat-head machine (hex drive) (6)
0043X	spring retainer/servo horn, steering	3937	Screws, 4x12mm button-head machine (hex drive) (6)
3736	Steering blocks, left & right (2) (requires 5x11x4mm bearings)	2542	Screws, 4x12mm countersunk machine (hex drive) (6)
3636A	Steering blocks, Rustler®/Stampede®/Bandit (2), 6061-T6	2546	Screws, 4x15mm countersunk machine (hex drive) (6)
•	aluminum (blue-anodized)/ 5x11mm ball bearings (4)	2743	Set (grub) screws, 3mm hardened (12)
3636G	Steering blocks, Rustler®/Stampede®/Bandit (2), 6061-T6	5529	Shim set, 3x7x1mm (2), 3x6x0.5mm (4), 3x7x2mm (2)/ hollow balls,
	aluminum (green-anodized)/ 5x11mm ball bearings (4)	2740	captured (4) Shoulder exercise steering helleranks (2x20mm can head machine)
3636T	Steering blocks, Rustler®/Stampede®/Bandit (2), 6061-T6	3742	Shoulder screws, steering bellcranks (3x30mm cap-head machine) (2)/ draglink shoulder screws (chrome) (2)
0000	aluminum (orange-anodized)/ 5x11mm ball bearings (4)	3642X	Shoulder screws, Ultra Shocks (3x12 hex drive) (6)
3636P	Steering blocks, Rustler®/Stampede®/Bandit (2), 6061-T6	2754	Stub axle pins (4)
3636V	aluminum (pink-anodized)/ 5x11mm ball bearings (4) Steering blocks, Bustler®/Stampede®/Bandit (2), 6061-T6	2746	Washers, 3x6mm metal (12)
3636X	Steering blocks, Rustler®/Stampede®/Bandit (2), 6061-T6 aluminum (red-anodized)/ 5x11mm ball bearings (4)		LED Lights
3631	Suspension arms (front) (2)		<u> </u>
3631X	Suspension arms, black, front, heavy duty (2)	3690	LED light bar, front (assembled)/ 3x8 BCS (2)/ 2.5x8 BCS (2)
3631A	Suspension arms, blue, front, heavy duty (2)		(requires front bumper #5835X for 2WD Slash®, #3635 for 2WD
3631G	Suspension arms, green, front, heavy duty (2)		Stampede®, #3630 for 2WD Bigfoot® No. 1, #6835X for 4WD Slash®, or #6735 for 4WD Stampede®)
3631T	Suspension arms, orange, front, heavy duty (2)	5893	LED light harness, rear (requires #5838, 6737X, or 6836 rear
3631R	Suspension arms, red, front, heavy duty (2)	0000	bumper)
2640	Suspension pins, 44mm (2) w/ E-clips	5894	LED light set, complete (includes front and rear bumpers with
3640	Suspension screw pin set, steel (hex drive) (requires part # 2640 for a		LED light bar, rear LED harness, & BEC Y-harness) (fits 2WD
	complete suspension pin set) (Rustler®, Stampede®, Bandit)		Slash®)
2532	Tie bar, fiberglass	2263	Y-harness, BEC to LED light set
1935	Turnbuckles, 36mm (2)		Meters e Fleetrenies
04004	T - - - - - - -		MOTORS & EIGHTOINGS
3139A	Turnbuckles, aluminum (blue-anodized), toe links, 59mm (2)	1726	Motors & Electronics Antenna, tube (1) vinyl antenna cap (1) wire retainer (1)
3139A	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum	1726 2260	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)
	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477)	1726 2260	
3139A 3139G	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2)		Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input
	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477)	2260	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage)
	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum	2260	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ 3300 motor) BL-2s™ Electronic Speed Control, waterproof (brushless)
3139G	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477)	3382 3383	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ 3300 motor) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake)
3139G 3139T	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477)	2260 3382	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ 3300 motor) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-
3139G	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2)	2260 3382 3383 3340	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ 3300 motor) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™
3139G 3139T	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum	22603382338333403790	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ 3300 motor) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed
3139G 3139T 3139P	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477)	3382 3383 3340 3790 2072A	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos)
3139G 3139T	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2)	2260 3382 3383 3340 3790 2072A 2252	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ Blectronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos)
3139G 3139T 3139P	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm	3382 3383 3340 3790 2072A 2252 2272	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ 3300 motor) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo)
3139G 3139T 3139P	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2)	2260 3382 3383 3340 3790 2072A 2252 2272 3384	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ 3300 motor) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless
3139G 3139T 3139P 3139X	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477)	2260 3382 3383 3340 3790 2072A 2252 2272 3384 3931	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ 3300 motor) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless Screws, 3x8mm flat-head machine (hex drive) (6)
3139G 3139T 3139P 3139X 3644	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash)	2260 3382 3383 3340 3790 2072A 2252 2272 3384 3931 2254	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ 3300 motor) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless Screws, 3x8mm flat-head machine (hex drive) (6) Servo case, aluminum (middle) (blue-anodized) (for 2250 servo)
3139G 3139T 3139P 3139X	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash) Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled	2260 3382 3383 3340 3790 2072A 2252 2272 3384 3931	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ 3300 motor) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless Screws, 3x8mm flat-head machine (hex drive) (6)
3139G 3139T 3139P 3139X 3644	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash) Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls)	2260 3382 3383 3340 3790 2072A 2252 2272 3384 3931 2254 2253	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ S300 motor) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless Screws, 3x8mm flat-head machine (hex drive) (6) Servo case, aluminum (middle) (blue-anodized) (for 2250 servo) Servo case, aluminum (middle) (red-anodized) (for 2255 servo)
3139G 3139T 3139P 3139X 3644	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash) Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled	2260 3382 3383 3340 3790 2072A 2252 2272 3384 3931 2254 2253	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ 3300 motor) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless Screws, 3x8mm flat-head machine (hex drive) (6) Servo case, aluminum (middle) (blue-anodized) (for 2250 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for
3139G 3139T 3139P 3139X 3644 3745	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash) Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls)	2260 3382 3383 3340 3790 2072A 2252 2272 3384 3931 2254 2253 2251	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ 3300 motor) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless Screws, 3x8mm flat-head machine (hex drive) (6) Servo case, aluminum (middle) (blue-anodized) (for 2250 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos)
3139G 3139T 3139P 3139X 3644	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash) Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls)	2260 3382 3383 3340 3790 2072A 2252 2272 3384 3931 2254 2253 2251 2271 2074 2075R	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ Brushless Power System, waterproof (brushless) (Fwd/rev/brake) Cooling fan, electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless Screws, 3x8mm flat-head machine (hex drive) (6) Servo case, aluminum (middle) (blue-anodized) (for 2250 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos) Servo case/gaskets (for 2070 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo, digital high-speed, metal gear (ball bearing), waterproof
3139G 3139T 3139P 3139X 3644 3745	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash) Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls)	2260 3382 3383 3340 3790 2072A 2252 2272 3384 3931 2254 2253 2251 2271 2074 2075R 2075	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ S300 motor) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless Screws, 3x8mm flat-head machine (hex drive) (6) Servo case, aluminum (middle) (blue-anodized) (for 2250 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos) Servo case/gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo, digital high-speed, metal gear (ball bearing), waterproof
3139G 3139T 3139P 3139X 3644 3745	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash) Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls)	2260 3382 3383 3340 3790 2072A 2252 2272 3384 3931 2254 2253 2251 2271 2074 2075R	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ 3300 motor) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless Screws, 3x8mm flat-head machine (hex drive) (6) Servo case, aluminum (middle) (blue-anodized) (for 2250 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos) Servo case/gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof
3139G 3139T 3139P 3139X 3644 3745 1926 1726 3935	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash) Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) Antenna caps, vinyl (2)/ antenna spool Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) Body clip (mounting clip), angled, 90-degrees (10)	2260 3382 3383 3340 3790 2072A 2252 2272 3384 3931 2254 2253 2251 2271 2074 2075R 2075 2250	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ Brushless Power System, waterproof (brushless) (fwd/rev/brake) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless Screws, 3x8mm flat-head machine (hex drive) (6) Servo case, aluminum (middle) (blue-anodized) (for 2250 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos) Servo case/gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof
3139G 3139T 3139P 3139X 3644 3745 1926 1726 3935 3935A	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash) Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) **Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) **Antenna caps, vinyl (2)/ antenna spool Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) Body clip (mounting clip), angled, 90-degrees (10) Body clip (mounting clip), angled, 90-degrees (black) (10)	2260 3382 3383 3340 3790 2072A 2252 2272 3384 3931 2254 2253 2251 2271 2074 2075R 2075	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ Brushless Power System, waterproof (brushless) (Fixed Selectronic Speed Control, waterproof (brushless) (Fixed Selectronic Speed Control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless Screws, 3x8mm flat-head machine (hex drive) (6) Servo case, aluminum (middle) (blue-anodized) (for 2250 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos) Servo case/gaskets (for 2070 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque 330 coreless, metal gear (ball bearing), waterproof
3139G 3139T 3139P 3139X 3644 3745 1926 1726 3935 3935A 3934	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash) Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) **TIWATE** Antenna caps, vinyl (2)/ antenna spool Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) Body clip (mounting clip), angled, 90-degrees (black) (10) Body clips, heavy duty (12)	2260 3382 3383 3340 3790 2072A 2252 2272 3384 3931 2254 2253 2251 2271 2074 2075R 2075 2250 2255	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ 3300 motor) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless Screws, 3x8mm flat-head machine (hex drive) (6) Servo case, aluminum (middle) (blue-anodized) (for 2250 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos) Servo case/gaskets (for 2070 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque 330 coreless, metal gear (ball bearing), waterproof
3139G 3139T 3139P 3139X 3644 3745 1926 1726 3935 3935A 3934 4859 1589 1633	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash) Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) Antenna caps, vinyl (2)/ antenna spool Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) Body clip (mounting clip), angled, 90-degrees (10) Body clip (mounting clip), angled, 90-degrees (black) (10) Body clips, heavy duty (12) CS 3x10 flathead (hex drive)	2260 3382 3383 3340 3790 2072A 2252 2272 3384 3931 2254 2253 2251 2271 2074 2075R 2075 2250 2255	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ Brushless Power System, waterproof (brushless) (Fwd/rev/brake) Cooling fan, electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless Screws, 3x8mm flat-head machine (hex drive) (6) Servo case, aluminum (middle) (blue-anodized) (for 2250 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255, 2255 servos) Servo case/gaskets (for 2070 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque 330 coreless, metal gear (ball bearing), waterproof Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof
3139G 3139T 3139P 3139X 3644 3745 1926 1726 3935 3935A 3934 4859 1589 1633 2745	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash) Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) **Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) **Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) **Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) **Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) **Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) **Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) **Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) **Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) **Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) **Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) **Turnbuckles, toe link, 59mm (89mm center to center) (2) (assembled with rod ends and hollow balls) **Turnbuckles, toe link, 59mm (89mm center to center)	2260 3382 3383 3340 3790 2072A 2252 2272 3384 3931 2254 2253 2251 2271 2074 2075R 2075 2250 2255	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ 3300 motor) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless Screws, 3x8mm flat-head machine (hex drive) (6) Servo case, aluminum (middle) (blue-anodized) (for 2250 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos) Servo case/gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque 330 coreless, metal gear (ball bearing), waterproof Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof
3139G 3139F 3139P 3139X 3644 3745 1926 1726 3935 3935A 3934 4859 1589 1633 2745 1747P	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash) Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) **Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) **Antenna caps, vinyl (2)/ antenna spool Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) Body clip (mounting clip), angled, 90-degrees (black) (10) Body clips, heavy duty (12) CS 3x10 flathead (hex drive) Double-sided adhesive tape (25mm x 25mm) E-clips/ C-rings Nuts, 3mm nylon locking (12) Nuts, 4mm flanged nylon locking (aluminum, pink anodized) (4)	2260 3382 3383 3340 3790 2072A 2252 2272 3384 3931 2254 2253 2251 2271 2074 2075R 2075 2250 2255	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ Brushless Power System, waterproof (brushless) (fwd/rev/brake) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless Screws, 3x8mm flat-head machine (hex drive) (6) Servo case, aluminum (middle) (blue-anodized) (for 2250 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos) Servo case/gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque 330 coreless, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof
3139G 3139F 3139P 3139X 3644 3745 1926 1726 3935 3935A 3934 4859 1589 1633 2745 1747P 3647	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash) Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) **Tirrangle** Antenna caps, vinyl (2)/ antenna spool Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) Body clip (mounting clip), angled, 90-degrees (black) (10) Body clips, heavy duty (12) CS 3x10 flathead (hex drive) Double-sided adhesive tape (25mm x 25mm) E-clips/ C-rings Nuts, 3mm nylon locking (12) Nuts, 4mm flanged nylon locking (steel, serrated) (8)	2260 3382 3383 3340 3790 2072A 2252 2272 3384 3931 2254 2253 2251 2271 2074 2075R 2075 2250 2255	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ Brushless Power System, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless Screws, 3x8mm flat-head machine (hex drive) (6) Servo case, aluminum (middle) (blue-anodized) (for 2250 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos) Servo case/ gaskets (for 2270 waterproof servo) Servo case/ gaskets (for 2056 and 2075 waterproof servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof
3139G 3139T 3139P 3139X 3644 3745 1926 1726 3935 3935A 3934 4859 1589 1633 2745 1747P 3647 1747	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash) Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) **Tilval**(F) Antenna caps, vinyl (2)/ antenna spool Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) Body clip (mounting clip), angled, 90-degrees (black) (10) Body clip (mounting clip), angled, 90-degrees (black) (10) Body clips, heavy duty (12) CS 3x10 flathead (hex drive) Double-sided adhesive tape (25mm x 25mm) E-clips/ C-rings Nuts, 3mm nylon locking (12) Nuts, 4mm flanged nylon locking (aluminum, pink anodized) (4) Nuts, 4mm flanged nylon locking (steel, serrated) (8) Nuts, 4mm nylon locking (10)	2260 3382 3383 3340 3790 2072A 2252 2272 3384 3931 2254 2253 2251 2271 2074 2075R 2075 2250 2255	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ Brushless Power System, waterproof (brushless) (fwd/rev/brake) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless Screws, 3x8mm flat-head machine (hex drive) (6) Servo case, aluminum (middle) (blue-anodized) (for 2250 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos) Servo case/gaskets (for 2070 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof
3139G 3139T 3139P 3139X 3644 3745 1926 1726 3935 3935A 3934 4859 1589 1633 2745 1747P 3647 1747R	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash) Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) Antenna caps, vinyl (2)/ antenna spool Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) Body clip (mounting clip), angled, 90-degrees (black) (10) Body clip (mounting clip), angled, 90-degrees (black) (10) Body clips, heavy duty (12) CS 3x10 flathead (hex drive) Double-sided adhesive tape (25mm x 25mm) E-clips/ C-rings Nuts, 3mm nylon locking (12) Nuts, 4mm flanged nylon locking (aluminum, pink anodized) (4) Nuts, 4mm flanged nylon locking (steel, serrated) (8) Nuts, 4mm nylon locking (10) Nuts, aluminum, flanged, serrated (4mm) (blue-anodized) (4)	2260 3382 3383 3340 3790 2072A 2252 2272 3384 3931 2254 2253 2251 2271 2074 2075R 2075 2250 2255 2270 2075X 3350R	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ Brushless Power System, waterproof (brushless) (fwd/rev/brake) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless Screws, 3x8mm flat-head machine (hex drive) (6) Servo case, aluminum (middle) (blue-anodized) (for 2250 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos) Servo case/gaskets (for 2050 and 2075 waterproof servo) Servo case/gaskets (for 2050 and 2075 waterproof servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque 330 coreless, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), w
3139G 3139T 3139P 3139X 3644 3745 1926 1726 3935 3935A 3935A 3935A 3935A 1747 1747P 3647 1747P 1747R 1747G	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash) Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) **TITURIC** Antenna caps, vinyl (2)/ antenna spool Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) Body clip (mounting clip), angled, 90-degrees (black) (10) Body clip (mounting clip), angled, 90-degrees (black) (10) Body clips, heavy duty (12) CS 3x10 flathead (hex drive) Double-sided adhesive tape (25mm x 25mm) E-clips/ C-rings Nuts, 3mm nylon locking (12) Nuts, 4mm flanged nylon locking (aluminum, pink anodized) (4) Nuts, 4mm flanged nylon locking (steel, serrated) (8) Nuts, 4mm nylon locking (10) Nuts, aluminum, flanged, serrated (4mm) (blue-anodized) (4) Nuts, aluminum, flanged, serrated (4mm) (green-anodized) (4)	2260 3382 3383 3340 3790 2072A 2252 2272 3384 3931 2254 2253 2251 2271 2074 2075R 2075R 2075 2250 2255 2270 2075X 3350R	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ 3300 motor) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless Screws, 3x8mm flat-head machine (hex drive) (6) Servo case, aluminum (middle) (blue-anodized) (for 2250 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos) Servo case/gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque (b
3139G 3139T 3139P 3139X 3644 3745 1926 1726 3935 3935A 3934 4859 1589 1633 2745 1747P 3647 1747R 1747G 1747T	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash) Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) ***LITIWATG** Antenna caps, vinyl (2)/ antenna spool Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) Body clip (mounting clip), angled, 90-degrees (10) Body clip (mounting clip), angled, 90-degrees (black) (10) Body clips, heavy duty (12) CS 3x10 flathead (hex drive) Double-sided adhesive tape (25mm x 25mm) E-clips/ C-rings Nuts, 3mm nylon locking (12) Nuts, 4mm flanged nylon locking (aluminum, pink anodized) (4) Nuts, 4mm flanged nylon locking (steel, serrated) (8) Nuts, 4mm nylon locking (10) Nuts, aluminum, flanged, serrated (4mm) (blue-anodized) (4) Nuts, aluminum, flanged, serrated (4mm) (green-anodized) (4) Nuts, aluminum, flanged, serrated (4mm) (green-anodized) (4)	2260 3382 3383 3340 3790 2072A 2252 2272 3384 3931 2254 2253 2251 2271 2074 2075R 2075 2250 2255 2270 2075X 3350R	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ 3300 motor) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless Screws, 3x8mm flat-head machine (hex drive) (6) Servo case, aluminum (middle) (blue-anodized) (for 2250 servo) Servo case, aluminum (middle) (red-anodized) (for 2255 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos) Servo case/gaskets (for 2070 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque (ball bea
3139G 3139F 3139P 3139X 3644 3745 1926 1726 3935 3935A 3934 4859 1589 1633 2745 1747P 3647 1747 1747R 1747G 1747G 1747A	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash) Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) Antenna caps, vinyl (2)/ antenna spool Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) Body clip (mounting clip), angled, 90-degrees (10) Body clip (mounting clip), angled, 90-degrees (black) (10) Body clips, heavy duty (12) CS 3x10 flathead (hex drive) Double-sided adhesive tape (25mm x 25mm) E-clips/ C-rings Nuts, 3mm nylon locking (12) Nuts, 4mm flanged nylon locking (aluminum, pink anodized) (4) Nuts, 4mm flanged nylon locking (steel, serrated) (8) Nuts, 4mm nylon locking (10) Nuts, aluminum, flanged, serrated (4mm) (blue-anodized) (4) Nuts, aluminum, flanged, serrated (4mm) (orange-anodized) (4) Nuts, aluminum, flanged, serrated (4mm) (orange-anodized) (4) Nuts, aluminum, flanged, serrated (4mm) (orange-anodized) (4)	2260 3382 3383 3340 3790 2072A 2252 2272 3384 3931 2254 2253 2251 2271 2074 2075R 2075 2250 2255 2270 2075X 3350R	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ 3300 motor) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless Screws, 3x8mm flat-head machine (hex drive) (6) Servo case, aluminum (middle) (blue-anodized) (for 2250 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof
3139G 3139T 3139P 3139X 3644 3745 1926 1726 3935 3935A 3934 4859 1633 2745 1747P 3647 1747R 1747R 1747R 1747G 1747A 1985	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash) Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) **Tiribical C** Antenna caps, vinyl (2)/ antenna spool Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) Body clip (mounting clip), angled, 90-degrees (black) (10) Body clips, heavy duty (12) CS 3x10 flathead (hex drive) Double-sided adhesive tape (25mm x 25mm) E-clips/ C-rings Nuts, 3mm nylon locking (12) Nuts, 4mm flanged nylon locking (aluminum, pink anodized) (4) Nuts, 4mm flanged nylon locking (steel, serrated) (8) Nuts, 4mm flanged nylon locking (steel, serrated) (8) Nuts, aluminum, flanged, serrated (4mm) (blue-anodized) (4) Nuts, aluminum, flanged, serrated (4mm) (orange-anodized) (4)	2260 3382 3383 3340 3790 2072A 2252 2272 3384 3931 2254 2253 2251 2271 2074 2075R 2075 2250 2255 2270 2075X 3350R	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ 3300 motor) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless Screws, 3x8mm flat-head machine (hex drive) (6) Servo case, aluminum (middle) (blue-anodized) (for 2250 servo) Servo case, aluminum (middle) (red-anodized) (for 2255 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos) Servo case/gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof
3139G 3139T 3139P 3139X 3644 3745 1926 1726 3935 3935A 3935A 3935A 3934 4859 1589 1633 2745 1747P 3647 1747 1747R 1747G 1747G 1747A	(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477) Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash) Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls) Antenna caps, vinyl (2)/ antenna spool Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) Body clip (mounting clip), angled, 90-degrees (10) Body clip (mounting clip), angled, 90-degrees (black) (10) Body clips, heavy duty (12) CS 3x10 flathead (hex drive) Double-sided adhesive tape (25mm x 25mm) E-clips/ C-rings Nuts, 3mm nylon locking (12) Nuts, 4mm flanged nylon locking (aluminum, pink anodized) (4) Nuts, 4mm flanged nylon locking (steel, serrated) (8) Nuts, 4mm nylon locking (10) Nuts, aluminum, flanged, serrated (4mm) (blue-anodized) (4) Nuts, aluminum, flanged, serrated (4mm) (orange-anodized) (4) Nuts, aluminum, flanged, serrated (4mm) (orange-anodized) (4) Nuts, aluminum, flanged, serrated (4mm) (orange-anodized) (4)	2260 3382 3383 3340 3790 2072A 2252 2272 3384 3931 2254 2253 2251 2271 2074 2075R 2075 2250 2255 2270 2075X 3350R	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage) BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ESC & BL-2s™ 3300 motor) BL-2s™ Electronic Speed Control, waterproof (brushless) (fwd/rev/brake) Cooling fan, electronic speed control, Velineon® VXL-3s or BL-2s™ Gear adapter, fixed Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo) Motor, BL-2s™ 3300, brushless Screws, 3x8mm flat-head machine (hex drive) (6) Servo case, aluminum (middle) (blue-anodized) (for 2250 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof

Page 4 Slash® Brushless: TQ™ 2.4GHz Radio (Model 58134-4) Parts List

. a.g		,	J = 194
2976	AC to DC adapter	6528	Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2-
2938X	Adapter, Traxxas® iD® LiPo battery (adapts Traxxas® iD®		channel (transmitter only)
	batteries to separate balance ports)	6529	Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 3-
5526	Antenna crimp nut, aluminum (blue-anodized)/ antenna nut tool	0500	channel (transmitter only)
5526R	Antenna crimp nut, aluminum (red-anodized)/ antenna nut tool	6530	Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4- channel (transmitter only)
2943	Battery charge indicators, green (4), grey (4), blue (4)	6511	Traxxas® Link Bluetooth® module
6548	Battery door, TQ 2.4 transmitter (replacement for #6516, 6517 transmitter)	6537	Wire retainers, gear cover/ 3x4mm BCS (2)
2923X	Battery, Power Cell, 3000mAh (NiMH, 7-C flat, 8.4V)	0007	
2926X	Battery, Power Cell, 3000mAh (NiMH, 7-C hump, 8.4V)		Ready-To-Race Model
2940X	Battery, Series 3 Power Cell, 3300mAh (NiMH, 7-C flat, 8.4V)	58134-4	Slash® Brushless: 1/10-Scale 2WD Short Course Racing Truck with
2941X	Battery, Series 3 Power Cell, 3300mAh (NiMH, 7-C hump, 8.4V)		TQ™ 2.4GHz radio system
2950X	Battery, Series 4 Power Cell, 4200mAh (NiMH, 7-C flat, 8.4V)		Rear Suspension
2951X	Battery, Series 4 Power Cell, 4200mAh (NiMH, 7-C hump, 8.4V)	5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)
2960X	Battery, Series 5 Power Cell, 5000mAh (NiMH, 7-C flat, 8.4V)	1951	Half shafts, long truck (external-splined (2) & internal-splined (2)/
2961X	Battery, Series 5 Power Cell, 5000mAh (NiMH, 7-C hump, 8.4V)	.00.	metal U-joints (4)
2985-2S	Battery/charger completer pack (includes #2985 charger (1),	3638	Shock tower (rear)
	#2827X 3000mAh 7.4V 2-cell 20C LiPo iD® Battery (1))	3752	Stub axle carriers (2) (requires 5x11x4mm bearings)
2260	BEC assembly (complete) (12.6 volts (3s LiPo) maximum input	3652A	Stub axle carriers, Rustler®/Stampede®/Bandit (2), 6061-T6
	voltage)		aluminum (blue-anodized)/ 5x11mm ball bearings (4)
2975	Charger, D/C, 4 amp (6 - 7 cell, 7.2 - 8.4 volt, NiMH)	3652G	Stub axle carriers, Rustler®/Stampede®/Bandit (2), 6061-T6
2972	Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery		aluminum (green-anodized)/ 5x11mm ball bearings (4)
	Identification	3652T	Stub axle carriers, Rustler®/Stampede®/Bandit (2), 6061-T6
2973	Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto		aluminum (orange-anodized)/ 5x11mm ball bearings (4)
2070	Battery Identification	3652P	Stub axle carriers, Rustler®/Stampede®/Bandit (2), 6061-T6
2970	Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with iD Auto Battery	20E2V	aluminum (pink-anodized)/ 5x11mm ball bearings (4)
2981	Identification Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto	3652X	Stub axle carriers, Rustler®/Stampede®/Bandit (2), 6061-T6 aluminum (red-anodized)/ 5x11mm ball bearings (4)
2001	Battery Identification	2753X	Stub axles, rear (2)
2985	Charger, EZ-Peak®, USB-C, 40W, NiMH/LiPo with iD® Auto	2555	Suspension arms, (rear) (2)
	Battery Identification	2555X	Suspension arms, black, rear, heavy duty (2)
2982	Charger, USB-C, 40W (6 - 7 cell, 7.2 - 8.4 volt, NiMH) (with iD®)	2555A	Suspension arms, blue, rear, heavy duty (2)
6525	Communication link, telemetry expander	2555G	Suspension arms, green, rear, heavy duty (2)
2978	Fuse, D/C charger, 5A (2) (for #2974, 2975, 2977)	2555T	Suspension arms, groun, roary duty (2)
2072A	Gear set (for 2070, 2075 servos)	2555R	Suspension arms, red, rear, heavy duty (2)
2252	Gear set, metal (for 2250, 2255 servos)	3640	Suspension screw pin set, steel (hex drive) (requires part # 2640 for a
2272	Gear set, metal (for 2270 waterproof servo)	00.0	complete suspension pin set) (Rustler®, Stampede®, Bandit)
2968X	LiPo cell voltage checker/balancer (includes #2938X adapter for	3644	Turnbuckles, camber link, 39mm (69mm center to center) (assembled
	Traxxas® iD® batteries)		with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on
2968	LiPo cell voltage checker/balancer (requires #2938X adapter for		Slash)
	Traxxas® iD® batteries)		Shock Oil
6554X	Mount, telemetry expander (fits Rustler®, Bandit, Slash 2WD)	5024	
6535	Mount, temperature sensor (electric motors)/ wire tie/ thermal	5031 5032	Oil, shock (20 wt, 200 cSt, 60cc) (silicone) Oil, shock (30 wt, 350 cSt, 60cc) (silicone)
	pad	5032	Oil, shock (40 wt, 500 cSt, 60cc) (silicone)
2912	Power adapter, AC, USB-C (45W) (110 volt, North America only)	5034	Oil, shock (50 wt, 600 cSt, 60cc) (silicone)
2916	Power cable, USB-C, 100W (high output), 5 ft. (1.5m)	5035	Oil, shock (60 wt, 700 cSt, 60cc) (silicone)
6519	Receiver, micro, TQ 2.4GHz (3-channel)	5036	Oil, shock (70 wt, 900 cSt, 60cc) (silicone)
6552	Seal kit, expander box (includes o-ring, seals, and silicone	5037	Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone)
6526	grease) Sensor, auto-detectable, temperature	5029	Shock oil bottle (60cc) (for mixing shock oil)
6527	, , , , , , , , , , , , , , , , , , ,	5038X	Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, &
652 <i>1</i>	Sensor, auto-detectable, voltage	00007	80 wt premium shock oils with spinning carousel rack)
6521	Sensor, RPM (long)/ 3x4mm BCS (1)/ 3x4 GS (1) Sensor, temperature and voltage (long)	5038	Spinning carousel rack
2254	Servo case, aluminum (middle) (blue-anodized) (for 2250 servo)		· · ·
2254	Servo case, aluminum (middle) (red-anodized) (for 2255 servo)		Shocks (Pro-level Aluminum)
2253 2251	Servo case, aluminum (middle) (red-anodized) (for 2255 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for	2664	Big Bore shock cylinder (long) (1)
2201	2250, 2255 servos)	5862	Big Bore shocks (hard-anodized & PTFE-coated T6 aluminum)
2271	Servo case/ gaskets (for 2270 waterproof servo)	0005	(assembled with TiN shafts and springs) (front & rear) (4)
2074	Servo case/gaskets (for 2056 and 2075 waterproof servos)	2660	Big-bore shocks (long) (hard-anodized & PTFE-coated T6
2075R	Servo, digital high-speed, metal gear (ball bearing), waterproof	2662	aluminum) (assembled with TiN shafts) w/o springs (2)
2075	Servo, digital high-torque (ball bearing), waterproof	2662	Big-bore shocks (xx-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled with TiN shafts) w/o springs (rear) (2)
2250	Servo, digital high-torque 330 coreless, metal gear (ball bearing),	2669	Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings
	waterproof	2003	& washers (2) (Big Bore Shocks)
2255	Servo, digital high-torque 400 brushless, metal gear (ball	1942	Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws
	bearing), waterproof		(2)
2270	Servo, digital high-torque, metal gear (ball bearing), waterproof	2742X	Rod ends, short (6)/ hollow balls (6)
2075X	Servo, digital high-torque, metal gear (ball bearing), waterproof	2667	Shock caps, aluminum (2) (Big Bore Shocks)
6553X	Telemetry Expander 2.0 and GPS module 2.0, TQi radio system	2362	Shock rebuild kit (for 2 shocks)
6550X	Telemetry expander 2.0, TQi radio system (for use only with	1664T	Shock shafts, hardened steel, titanium nitride coated (long) (2)
	#6551X GPS module)	2656T	Shock shafts, hardened steel, titanium nitride coated (xx-long)
6551X	Telemetry GPS module 2.0, TQi radio system (for use only with		(2)
	#6550X telemetry expander)	1664	Shock shafts, steel, chrome finish (long) (2)
6538	Telemetry trigger magnet holders, spur gear/ magnet, 5x2mm (1)/	2656	Shock shafts, steel, chrome finish (xx-long) (2)
0=46	3x8mm CCS (3)/ 3x10mm CCS (3)	1765	Silicone diaphragms (4)
6540	Telemetry trigger magnet, 5X2mm (1)	2668	Spring retainers, upper & lower (2)/ spring pre-load spacers:
6509R	TQi 2.4 GHz High Output radio system, 2-channel, Traxxas® Link		1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore
65070	enabled, TSM® (2-ch transmitter, 5-ch micro receiver)		Shocks)
6507R	TQi 2.4 GHz High Output radio system, 4-channel with Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro	5860	Springs, front (white) (progressive rate) (2) (for Slash big bore
			shocks)
	receiver)	FOFO	Continue year (white) /pre
6516	receiver) Transmitter, TQ 2.4GHz, 2-channel (transmitter only)	5859	Springs, rear (white) (progressive rate) (2) (for Slash big bore
6516	receiver) Transmitter, TQ 2.4GHz, 2-channel (transmitter only)	5859	Springs, rear (white) (progressive rate) (2) (for Slash big bore shocks)

Page 5 Slash® Brushless: TQ™ 2.4GHz Radio (Model 58134-4) Parts List

	Shocks (Ultra Shocks)	3743A	Steering bellcranks, drag link (blue-anodized 6061-T6 aluminum)/
3765A 3766A	Body, Ultra Shock (long) (grey) (2) Body, Ultra Shock (XXL) (grey) (2)	3743G	5x8mm ball bearings (4)/ hardware (assembled) Steering bellcranks, drag link (green-anodized 6061-T6
1942	Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws	3743T	aluminum)/ 5x8mm ball bearings (4)/ hardware (assembled) Steering bellcranks, drag link (orange-anodized 6061-T6
2742X	(2) Rod ends, short (6)/ hollow balls (6)	3743P	aluminum)/ 5x8mm ball bearings (4)/ hardware (assembled) Steering bellcranks, drag link (pink-anodized 6061-T6 aluminum)/
3767 8361	Shock caps (2)/ shock bottoms (2) Shock caps (black) (4) (assembled with hollow balls)	3743X	5x8mm ball bearings (4)/ hardware (assembled)
3767A	Shock caps, aluminum (blue-anodized) (4) (fits all Ultra Shocks)		Steering bellcranks, drag link (red-anodized 6061-T6 aluminum)/ 5x8mm ball bearings (4)/ hardware (assembled)
3767G 3767T	Shock caps, aluminum (green-anodized) (4) (fits all Ultra Shocks) Shock caps, aluminum (orange-anodized) (4) (fits all Ultra	6845X	Steering bellcranks/ servo saver/ servo saver spring/ servo spring retainer/servo horn, steering
3767P	Shocks) Shock caps, aluminum (pink-anodized) (4) (fits all Ultra Shocks)	1935 3139A	Turnbuckles, 36mm (2)
3767X	Shock caps, aluminum (red-anodized) (4) (fits all Ultra Shocks)	3139A	Turnbuckles, aluminum (blue-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum
2362 1664T	Shock rebuild kit (for 2 shocks) Shock shafts, hardened steel, titanium nitride coated (long) (2)	3139G	wrench #5477) Turnbuckles, aluminum (green-anodized), toe links, 59mm (2)
2656T	Shock shafts, hardened steel, titanium nitride coated (xx-long) (2)		(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477)
1664	Shock shafts, steel, chrome finish (long) (2)	3139T	Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2)
2656 3642X	Shock shafts, steel, chrome finish (xx-long) (2) Shoulder screws, Ultra Shocks (3x12 hex drive) (6)		(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477)
1765	Silicone diaphragms (4)	3139P	Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum
3769 3768	Spring pre-load spacers: 1mm (4)/ 2mm (2)/ 4mm (2)/ 8mm (2) Spring retainers, upper & lower (2)/ piston head set (2-hole (2)/ 3-hole	24207	wrench #5477)
2458P	(2)) Springs (front) (pink) (2)	3139X	Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm
2458A	Springs (front) (white) (2)	3745	aluminum wrench #5477) Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled
3757T 2458	Springs, blue (rear) (2) Springs, front (black) (2)		with rod ends and hollow balls)
5857P	Springs, front (pink) (progressive rate) (2)	2746	Washers, 3x6mm metal (12) SUSPENSION LINKAGE
5857 3757A	Springs, front (white) (progressive rate) (2) Springs, green (rear) (2)	5525	Rod ends (12)/ hollow balls (12)
3757P	Springs, pink (rear) (2)	5347	Rod ends, Revo® (large) with hollow balls (12)
3757	Springs, rear (black) (2)	3739	Screw pin set (Rustler®/ Bandit/ Stampede®)
5858P 5858	Springs, rear (pink) (progressive rate) (2)	5529	Shim set, 3x7x1mm (2), 3x6x0.5mm (4), 3x7x2mm (2)/ hollow balls, captured (4)
4957	Springs, rear (white) (progressive rate) (2) Springs, red (for Ultra Shocks only) (2.5 rate) (f/r) (2)	2640	Suspension pins, 44mm (2) w/ E-clips
3757X	Springs, white (rear) (2)	3640	Suspension screw pin set, steel (hex drive) (requires part # 2640 for a
3760	Ultra Shocks (black) (long) (complete w/ spring pre-load spacers & springs) (front) (2)	3139A	complete suspension pin set) (Rustler®, Stampede®, Bandit) Turnbuckles, aluminum (blue-anodized), toe links, 59mm (2)
3762	Ultra Shocks (black) (xx-long) (complete w/ spring pre-load spacers & springs) (rear) (2)		(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477)
3760A	Ultra Shocks (grey) (long) (complete w/ spring pre-load spacers & springs) (2)	3139G	Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum
3762A	Ultra Shocks (grey) (xx-long) (complete w/ spring pre-load spacers & springs) (rear) (2)	3139T	wrench #5477) Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2)
	Slipper Clutch Components		(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477)
3793	Input shaft (slipper shaft) / spring pin	3139P	Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2)
5552X	Rebuild kit, slipper clutch (steel disc/ friction pads (3)/ spring (2)/ pin/ 4.0mm NL (1)/ 5.0mm NL (1))		(assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477)
2554 5556	Screws, 3x6mm caphead machine (hex drive) (6) Slipper pressure plate & hub (aluminum alloy)	3139X	Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm
	Spur Gears & Pinion Gears	3644	aluminum wrench #5477) Turnbuckles, camber link, 39mm (69mm center to center) (assembled
3790	Gear adapter, fixed	3044	with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on
2416	Gear, 16-T pinion (48-pitch) / set screw	2745	Slash)
1918 2419	Gear, 18-T pinion (48-pitch) / set screw Gear, 19-T pinion (48-pitch) / set screw	3745	Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls)
2422	Gear, 22-T pinion (48-p) (fits 3mm shaft)/ set screw		Team Traxxas Items
2423	Gear, 23-T pinion (48-pitch) (fits 3mm shaft)/ set screw	9916	Backpack, RC car carrier, 12" x 12" x 24" (fits TRX-4 & similar)
2426 4728	Gear, 26-T pinion (48-pitch) (fits 3mm shaft)/ set screw	2514	Decal sheet, racing sponsors
2431	Gear, 28-T pinion (48-pitch) (fits 3mm shaft)/ set screw Gear, 31-T pinion (48-pitch) (fits 3mm shaft)/ set screw	9917	Duffel bag, medium, 30" x 12" x 12" (fits 1/10 Slash®, TRX-4®, &
4725	Gear, pinion (25-tooth) (48-pitch) / set screw	9950	similar) Official Team Traxxas® racing decal set(flag logo/ 6-color)
4683	Spur gear, 83-tooth (48-pitch) (for models with Torque Control slipper clutch)	9909	Traxxas® racing banner, red & black (3x7 feet)
4686	Spur gear, 86-tooth (48-pitch) (for models with Torque-Control slipper clutch)	5110	Tires & Wheels
4690	Spur gear, 90-tooth (48-pitch) (for models with Torque-Control	5116 5854	Ball bearings, blue rubber sealed (5x11x4mm) (2) Hub retainer, 17mm hubs, M4 X 0.7 (4) (use with #5853X, #6856X,
	slipper clutch) Steering Components	1747P	#6469) Nuts, 4mm flanged nylon locking (aluminum, pink anodized) (4)
2728	Ball bearings (5x8x2.5mm) (2)	3647	Nuts, 4mm flanged nylon locking (steel, serrated) (8)
2545	Bushings (plastic) (5x8x2.5mm) (4)	1747R	Nuts, aluminum, flanged, serrated (4mm) (blue-anodized) (4)
1985	PTFE-coated Washers, 5x8x0.5mm (20) (use with ball bearings)	1747G	Nuts, aluminum, flanged, serrated (4mm) (green-anodized) (4)
2742	Rod ends, long (6)/ hollow ball connectors (6)	1747T 1747A	Nuts, aluminum, flanged, serrated (4mm) (orange-anodized) (4) Nuts, aluminum, flanged, serrated (4mm) (red-anodized) (4)
5347 3744	Rod ends, Revo® (large) with hollow balls (12) Servo saver w/ adapters	1985	PTFE-coated Washers, 5x8x0.5mm (20) (use with ball bearings)
3742	Shoulder screws, steering bellcranks (3x30mm cap-head machine)	1647	Silicone Grease
	(2)/ draglink shoulder screws (chrome) (2)	2754	Stub axle pins (4)
3743	Steering bellcranks (l&r)/ draglink		

Page 6 Slash® Brushless: TQ™ 2.4GHz Radio (Model 58134-4) Parts List

90 0		,	
5882R	Tire & wheel assy, glued (S1 compound) (SCT Split-Spoke satin chrome, black beadlock style wheels, Kumho tires, foam inserts) (2) (2WD front)	5891	Tires & wheels, assembled, glued (SCT Split-Spoke black, satin chrome beadlock style wheels, paddle tires, foam inserts) (2) (4WD f/r, 2WD rear) (TSM® rated)
6874R	Tire & wheel assy, glued (S1 compound) (SCT Split-Spoke satin chrome, black beadlock wheel, Kumho tire, insert) (2) (4WD front/rear, 2WD rear only)	6873	Tires & wheels, assembled, glued (SCT Split-Spoke satin chrome, black beadlock style wheels, BFGoodrich® Mud- Terrain™ T/A® KM2 tires, foam inserts) (2) (4WD f/r, 2WD rear)
5877R	Tire & wheel assy, glued (S1 compound) (SCT Split-Spoke, chrome red beadlock wheel, BFGoodrich® Mud-Terrain™ T/A® KM2 tires, inserts) (2) (2WD front)	5875	(TSM® rated) Tires & wheels, assembled, glued (SCT, satin chrome wheels, beadlock type (dual profile 2.2" outer 3.0" inner), SCT off-road
6873R	Tire & wheel assy, glued (S1 compound) (SCT SS, chrome red	5070	tires, foam inserts) (2) (Front)
	beadlock wheel, BFGoodrich® Mud-Terrain™ T/A® KM2 tire, inserts) (2) (4WD f/r, 2WD rear)	5873	Tires & wheels, assembled, glued (SCT, satin chrome wheels, beadlock type (dual profile 2.2" outer 3.0" inner), SCT off-road
6873X	Tire & wheel assy, glued (S1 compound) (SCT SS, satin chrome black beadlock wheel, BFGoodrich® Mud-Terrain™ T/A® KM2 tire, inserts) (2) (4WD f/r, 2WD rear)	5873A	tires, foam inserts) (2) (Rear) (TSM® rated) Tires & wheels, assembled, glued (SCT, satin chrome wheels, red beadlock, (dual profile 2.2" outer 3.0" inner), SCT off-road
5869	Tire & wheel assy, glued (SCT chrome, red beadlock style wheels, BFGoodrich® Mud-Terrain™ T/A® KM2 tires, foam inserts) (2) (2WD front)	5873R	tires, foam inserts) (2) (Rear) Tires & wheels, assembled, glued (SCT, satin chrome, red beadlock wheels, ultra soft S1 compound off-road racing tires,
5867	Tire & wheel assy, glued (SCT chrome, red beadlock style wheels, BFGoodrich® Mud-Terrain™ T/A® KM2 tires, inserts)	6871	foam inserts) (2) (2WD Rear, 4WD F/R) Tires, BFGoodrich® Mud-Terrain™ T/A® KM2 (dual profile 4.3x1.7-
5881X	(2)(4WD front/rear, 2WD rear only) Tire & wheel assy, glued (SCT satin chrome, beadlock style	6871R	2.2/3.0") (2)/ foam inserts (2) Tires, BFGoodrich® Mud-Terrain™ T/A® KM2 , ultra-soft (S1 off-
5880X	wheels, Kumho tires, foam inserts) (2) (2WD front only) Tire & wheel assy, glued (SCT satin chrome, beadlock style		road racing compound) (dual profile 4.3x1.7- 2.2/3.0") (2)/ foam inserts (2)
OOOOX	wheels, Kumho tires, foam inserts) (2) (4WD front/rear, 2WD rear	6870	Tires, Kumho (dual profile 4.3x1.7- 2.2/3.0") (2)/ foam inserts (2)
5881	only) Tire & wheel assy, glued (SCT satin chrome, black beadlock	6870R	Tires, Kumho, ultra-soft (S1 off-road racing compound) (dual profile 4.3x1.7- 2.2/3.0") (2)/ foam inserts (2)
0001	style wheels, Kumho tires, foam inserts) (2) (2WD front)	5871	Tires, off-road racing, SCT dual profile 4.3x1.7- 2.2/3.0" (2)/ foam
5880	Tire & wheel assy, glued (SCT satin chrome, black beadlock style wheels, Kumho tires, foam inserts) (2) (4WD front/rear,	5871R	inserts (2) Tires, Ultra soft, S1 compound for off-road racing, SCT dual
	2WD rear only)		profile 4.3x1.7- 2.2/3.0" (2)/ foam inserts (2)
5875X	Tire & wheel assy, glued (SCT satin chrome, black beadlock style wheels, SCT off-road racing tires, foam inserts) (2) (2WD	3654 1654	Wheel hubs, hex (front) (tall offset) (2)/ axle pins (2.5x10mm) (2)
	front)	5853X	Wheel hubs, hex (rear) (2)/ stub axle pins (2) Wheel hubs, splined, 17mm, short (2), long (2) (blue-anodized) /
5878	Tire & wheel assy, glued (SCT satin chrome, black beadlock		wheel nuts, splined, 17mm (blue-anodized) (4)/ hub retainer M4 X
	wheel, BFGoodrich® Mud-Terrain™ T/A® KM2 tire, insert) (2)(4WD front/rear, 2WD rear only)	5353	0.7 (4)/ axle pin (4) (Slash 2WD) Wheel nuts, splined, 17mm (blue-anodized) (4)
6873A	Tire & wheel assy, glued (SCT Split-Spoke chrome, red beadlock	5480X	Wheel wrench, splined, 17mm
	style wheel, BFGoodrich® Mud-Terrain™ T/A® KM2 tire, inserts) (2) (4WD f/r, 2WD rear)	5868A	Wheels, SCT chrome, blue beadlock style, dual profile (2.2" outer
5882	Tire & wheel assy, glued (SCT Split-Spoke satin chrome, black	5870A	3.0" inner) (2) (4WD front/rear, 2WD rear only) Wheels, SCT chrome, blue beadlock style, dual profile (2.2"
	beadlock style wheels, Kumho tires, foam inserts) (2) (2WD front)		outer, 3.0" inner) (2) (2WD front only)
6874	Tire & wheel assy, glued (SCT Split-Spoke satin chrome, black	5868	Wheels, SCT chrome, red beadlock style, dual profile (2.2" outer 3.0" inner) (2) (4WD front/rear, 2WD rear only)
	beadlock style wheels, Kumho tires, foam inserts) (2) (4WD front/rear, 2WD rear only)	5874	Wheels, SCT satin chrome, beadlock style, dual profile (2.2" outer 3.0" inner) (2) (Front)
5885A	Tire & wheel assy, glued (SCT Split-Spoke, black, blue beadlock wheels, BFGoodrich® Mud-Terrain™ T/A® KM2 tires, inserts) (2) (2WD Front)	5872	Wheels, SCT satin chrome, beadlock style, dual profile (2.2" outer 3.0" inner) (2) (Rear)
5883A	Tire & wheel assy, glued (SCT Split-Spoke, black, blue beadlock wheels, BFGoodrich® Mud-Terrain™ T/A® KM2 tire, inserts) (2)	5874X	Wheels, SCT satin chrome, black beadlock style, dual profile (2.2" outer 3.0" inner) (2) (2WD front only)
	(4WD f/r, 2WD rear)	5872X	Wheels, SCT satin chrome, black beadlock style, dual profile (2.2" outer 3.0" inner) (2) (4WD front/rear, 2WD rear only)
5885	Tire & wheel assy, glued (SCT Split-Spoke, black, satin chrome beadlock wheels, BFGoodrich® Mud-Terrain™ T/A® KM2 tires, inserts) (2) (2WD Front)	5874A	Wheels, SCT satin chrome, red beadlock style, dual profile (2.2" outer 3.0" inner) (Front) (2)
5883	Tire & wheel assy, glued (SCT Split-Spoke, black, satin chrome	5886A	Wheels, SCT split-spoke, black, blue beadlock style, dual profile (2.2" outer 3.0" inner) (2WD front) (2)
	beadlock wheels, BFGoodrich® Mud-Terrain™ T/A® KM2 tire, inserts) (2) (4WD f/r, 2WD rear)	5884A	Wheels, SCT Split-Spoke, black, blue beadlock style, dual profile
5877A	Tire & wheel assy, glued (SCT Split-Spoke, chrome red beadlock wheels, BFGoodrich® Mud-Terrain™ T/A® KM2 tires, inserts)	5886	(2.2" outer 3.0" inner) (4WD f/r, 2WD rear) (2) Wheels, SCT Split-Spoke, black, satin chrome beadlock style, dual
E077	(2) (2WD Front) Tire & wheel assy, glued (SCT Split-Spoke, satin, black beadlock	5884	profile (2.2" outer 3.0" inner) (2WD front) (2) Wheels, SCT Split-Spoke, black, satin chrome beadlock style, dual
5877	wheel, BFGoodrich® Mud-Terrain™ T/A® KM2 tire, foam	6872X	profile (2.2" outer 3.0" inner) (4WD f/r, 2WD rear) (2) Wheels, SCT Split-Spoke, chrome, green beadlock style, dual
5864	inserts) (2) (2WD Front) Tire & wheel assy, glued (SCT, black, orange beadlock wheels,	6872A	profile (2.2" outer 3.0" inner) (4WD front/rear, 2WD rear) (2) Wheels, SCT Split-Spoke, chrome, red beadlock style, dual
5863	SCT off-road racing tires, foam inserts) (2) (2WD Front) Tire & wheel assy, glued (SCT, black, orange beadlock wheels,		profile (2.2" outer 3.0" inner) (4WD front/rear, 2WD rear) (2)
	SCT off-road racing tires, foam inserts) (2) (4WD f/r, 2WD rear) (TSM® rated)	5876	Wheels, SCT Split-Spoke, satin chrome, black beadlock style, dual profile (2.2" outer 3.0" inner) (2WD front) (2)
5865	Tire & wheel assy, glued (SCT, chrome, green beadlock wheel, BFGoodrich® Mud-Terrain™ T/A® KM2 tire, foam inserts) (2) (2WD front only)	6872	Wheels, SCT Split-Spoke, satin chrome, black beadlock style, dual profile (2.2" outer 3.0" inner) (4WD front/rear, 2WD rear only) (2)
6876	Tire & wheel assy, glued (SCT, chrome, green beadlock wheel,	5870X	Wheels, SCT, black, orange beadlock style, dual profile (2.2"
	BFGoodrich® Mud-Terrain™ T/A® KM2 tire, foam inserts) (2) (4WD front/rear, 2WD rear only)	5868X	outer 3.0" inner) (2WD front) (2) Wheels, SCT, black, orange beadlock style, dual profile (2.2"
5873X	Tire & wheel assy, glued (SCTsatin chrome, black beadlock style wheels, SCT off-road racing tires, foam inserts) (2) (4WD	5866	outer 3.0" inner) (4WD f/r, 2WD rear) (2) Wheels, SCT, chrome, green beadlock style, dual profile (2.2"
58501	front/rear, 2WD rear only) Tires & wheels assembled glued (SCT chrome blue headlock	6875	outer 3.0" inner) (2) (2WD front only) Wheels, SCT, chrome, green beadlock style, dual profile (2.2"
5869A	Tires & wheels, assembled, glued (SCT chrome, blue beadlock style wheels, BFGoodrich® Mud-Terrain™ T/A® KM2 tires, foam inserts) (2) (2)WD front)		outer 3.0" inner) (2) c
5867A	inserts) (2) (2WD front) Tires & wheels, assembled, glued (SCT chrome, blue beadlock	5440	Transmission Components
	style wheels, BFGoodrich® Mud-Terrain™ T/A® KM2 tires, foam	5116 3792	Ball bearings, blue rubber sealed (5x11x4mm) (2) Cover, gear/ rubber gear cover plug/ 3x6 RM (2)
	inserts) (2) (4WD front/rear, 2WD rear only)	3790	Gear adapter, fixed

Page 7 Slash® Brushless: TQ™ 2.4GHz Radio (Model 58134-4) Parts List

3139P

3139X

3644

3745

3691	Gearbox halves (L&R) (black) w/ idler gear shaft
3691A	Gearbox halves (L&R) (grey) w/ idler gear shaft
5148	Grease, white lithium
9492	Idler gear, 30-tooth/ idler gear shaft (steel)
3696	Idler gear, steel (30-tooth)
9494	Input gear, 22-tooth/ input shaft (transmission) (heavy duty) (fits Bandit®, Rustler®, Stampede®, Slash® 2WD)
3793	Input shaft (slipper shaft) / spring pin
2381X	Main diff with steel ring gear/ side cover plate/ screws (Bandit, Stampede®, Rustler®)
1552	Motor screws (3x8mm hex cap) (6)/washers (6)/ wrench
2382	Planet gears (4)/ planet shafts (4)/ sun gears (2)/sun gear alignment shaft (1) all hardened steel
2388X	Planetary gear differential with steel ring gear (complete) (fits Bandit, Stampede®, Rustler®)
9495	Pro Series Magnum 272R™ Transmission, complete (assembled) (fits 1/10-scale 2WD Rustler®, Bandit®, Stampede®, Slash®)
5552X	Rebuild kit, slipper clutch (steel disc/ friction pads (3)/ spring (2)/ pin/ 4.0mm NL (1)/ 5.0mm NL (1))
2554	Screws, 3x6mm caphead machine (hex drive) (6)
3931	Screws, 3x8mm flat-head machine (hex drive) (6)
1647	Silicone Grease
5556	Slipper pressure plate & hub (aluminum alloy)
3195	Top drive gear, steel (22-tooth)
3695	Transmission, complete (fits 1/10-scale 2WD Rustler®, Bandit®, Stampede®, Slash®)
	Travvae Toole

II	'n	\.\	F	S	TO	0	S

3433X	Body reamer (aluminum handle)
3433	Body reamer (plastic handle)
3436	Cap, body reamer
3432	Scissors, curved tip
3431	Scissors, straight tip
8712	Speed Bit Essentials Set, hex and nut driver, 7-piece, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm, and 8.0mm), 1/4" drive
8720	Speed bit handle, large (overmolded)
8721	Speed bit handle, medium (one piece)
8722	Speed bit handle, premium (rubber overmold)
8710	Speed Bit Master Set, hex and nut driver, 13-piece, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm, 3.0mm), and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive
8711	Speed Bit Master Set, hex driver, 7-piece straight and ball end, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm, 2.5mm, 3.0mm), 1/4" drive
8719	Speed Bit Master Set, nut driver, 6-piece, includes premium handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive
8716	Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4" drive
8716X	Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm, 3.0mm) 1/4" drive
8715	Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm, 2.5mm), 1/4" drive
8715X	Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm, 2.5mm, 3.0mm), 1/4" drive
8714	Speed Bit Set, screwdriver, 3-piece straight (3mm slotted, #1 Phillips, and #2 Phillips bits), 1/4" drive
2748R	Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench)
3415	Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle)

Turnbuckles & Threaded Rods

5525	Rod ends (12)/ hollow balls (12)
5347	Rod ends, Revo® (large) with hollow balls (12)
3139A	Turnbuckles, aluminum (blue-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477)
3139G	Turnbuckles, aluminum (green-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477)
3139T	Turnbuckles, aluminum (orange-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477)

Turnbuckles, aluminum (pink-anodized), toe links, 59mm (2) (assembled w/ rod ends & hollow balls) (requires 5mm aluminum wrench #5477)

Turnbuckles, aluminum (red-anodized), toe links, 59mm (2) (assembled with rod ends & hollow balls) (requires 5mm aluminum wrench #5477)

Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash)

Turnbuckles, toe link, 59mm (78mm center to center) (2) (assembled with rod ends and hollow balls)

If you have questions or need technical assistance, call Traxxas at:

1-888-TRAXXAS

(1-888-872-9927) (U.S. residents only)

For orders, calls outside the U.S., and other information, call 972-549-3000, or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com

TRAXXAS.COM